

## CLPT-6016

### Compact Sandwich Prep Table Self-Contained Solid Doors



Models listed to the applicable UL, CSA and NSF standards by an approved NRTL. Consult the factory or unit data plate for additional information.

### STANDARD PRODUCT FEATURES

- Self-Contained Rear-Mounted Refrigeration System Using R-290 Refrigerant
- High Quality Stainless Steel Construction
- Anodized Aluminum Interior
- LED Display Control for Accuracy and Easy Monitoring
- Stay Open Door Feature at 105°
- Capillary Tube Metering Device
- 12" Deep, 3/4" Thick, Full Length Removable Cutting Board
- NSF Approved White Polyethylene Board
- Maintains Cabinet Temperature of 32°F to 41°F
- Insulated Hood
- Tested to NSF7 Requirements
- Accommodates 6" Deep Pans
- Top Cut-Out Accommodates 1/6 Size Pans (4" deep plastic pans provided)
- Two (2) Adjustable, Heavy Duty Epoxy Coated Shelves Per Section
- Field Reversible Door(s)
- Set of Four (4) 4" H Casters, Front Two w/ Locks, Pre-installed on Device
- Gasket-Protecting Retainer
- High-Density, Non-CFC Foamed in Place Polyurethane Insulation

### ACCESSORIES & OPTIONS (Available at Extra Cost)

- + Additional Epoxy Coated Shelves on Pilasters
- + Set of Four (4) 6" High Legs
- + Set of Four (4) 6" High Casters
- + Set of Four (4) 2-3/4" High Casters

### AVAILABLE CONFIGURATIONS

#### MODELS

CLPT-6016-SD-LR

CLPT-6016-SD-LL

CLPT-6016-SD-RR

#### HINGING

Solid Doors, Left/Right

Solid Doors, Left/Left

Solid Doors, Right/Right


| Model     | Doors | Shelves | Pans (1/6) | Dimensions L x D x H (in.) | Voltage  | Amps | NEMA    | Cu. Ft. |
|-----------|-------|---------|------------|----------------------------|----------|------|---------|---------|
| CLPT-6016 | 2     | 4       | 16         | 60.56 x 32.75 x 40*        | 115/60/1 | 2.6  | 5 - 15P | N/A     |

\*Note: 40 in. height without casters


Approved by \_\_\_\_\_ Date \_\_\_\_\_ Approved by \_\_\_\_\_ Date \_\_\_\_\_

## MODEL - CLPT-6016


Solid Door Models



**ELEVATION**



**SIDE VIEW**



**PAN LAYOUT**

## SPECIFICATIONS

### CONSTRUCTION, HARDWARE, INSULATION

Cabinet exterior front, sides, and door(s) are constructed of stainless steel. Cabinet interior is constructed of anodized aluminum. 1/6 size plastic pans and a set of four (4) 4" high casters are included. Doors are equipped with a gasket protecting retainer. Both the cabinet and door(s) are insulated with an average of 2-3/8" thick high density, non-CFC, foamed in place polyurethane insulation.

### REFRIGERATION SYSTEM

A rear mounted, self-contained, balanced refrigeration system using environmentally friendly, low GWP R-290 refrigerant is provided. It features an easy to clean rear facing condenser, capillary tube metering device, and an air-cooled hermetic compressor. A 9' cord and plug is provided. Standard operating temperature is 32°F to 41°F. Energy efficient refrigeration system maintains safe product temperatures. Condenser is located in back of unit for easy maintenance and zero clearance.

### CONTROLLER

The easy to use electronic digital control is supplied standard. It includes a 3-Digit LED display, and a Fahrenheit or Celsius temperature scale display capability.

### INTERIOR

Standard interior arrangements include two (2) epoxy coated wire shelves per section, mounted on pilasters. Recommended load limit per shelf should not exceed 150 lbs.

### WARRANTY

Both a 6 Year Parts & Labor Warranty and additional 1 Year on Compressor Parts Warranty are supplied standard.

| MODELS                     | CLPT-6016                    |
|----------------------------|------------------------------|
| <b>ELECTRICAL DATA</b>     |                              |
| Voltage                    | 115/60/1                     |
| Full Load Amperes          | 2.6                          |
| <b>REFRIGERATION DATA</b>  |                              |
| Refrigerant                | R-290                        |
| Refrigerant Charge oz.     | 3.0 (85 g)                   |
| BTU/HR <sup>1</sup>   H.P. | 1800   1/5                   |
| <b>SHIPPING DATA</b>       |                              |
| Depth Crated in.           | 35 (88.9 cm)                 |
| Height Crated in.          | 49 (124.5 cm)                |
| Length Crated in.          | 65 (165.1 cm)                |
| Volume Crated cu. ft.      | 64.5 (1827 cm <sup>3</sup> ) |
| Net Weight lbs.            | 352 (159.6 kg)               |
| Gross Weight lbs.          | 391 (177.4 kg)               |

### NOTES:

1. BTU/HR based on a 90°F ambient and 20°F evaporator

Equipped with one NEMA 5-15P Plug

